

Nylotube[®]

Nylon-12 Tubing



ESOP Employee Owned
for Your Benefit

Fluid Transfer Specialists[®]

Nylon-12 Tubing



- Very low moisture absorption: 1.4% maximum (at 73°F)
- Will not become brittle or swell because of water
- Excellent resistance to flexural fatigue, tube vibration, and movement
- Lightweight with excellent bend radii and pressure ratings
- Resists crushing, abrasion, and cracking
- Heat and light stabilized
- Free of BPA, conflict minerals, phthalates and latex
- REACH and RoHS compliant
- Available in semi-rigid or flexible grade, inch and millimeter sizes, and in colors

Notes

NYLOTUBE is resistant to most solvents, alkalis, oils, greases, petroleum products, fungi, and molds. It has generally good resistance to dilute mineral and organic acids, but in cases where NYLOTUBE is being used in critical applications or aggressive environments, in-plant tests are always recommended.

NYLOTUBE is manufactured from heat- and light-stabilized materials.

Nylon brittleness is usually caused by cycles of water absorption and depletion. NYLOTUBE is not dependent on moisture for flexibility, so life expectancy is increased and the risk of brittleness greatly reduced.

Contact us for information on nylon-11 tubing and custom coiled nylon.

Recommended Fittings

- Newloc® push-to-connect fittings

Physical Properties**

	SEMI-RIGID GRADE	FLEXIBLE GRADE
Hardness, Shore D ±5	72	63
Tensile Strength, psi	>7252	>7252
Elongation at Break, %	>200	>200
Brittle Temperature, °F	-94	-94
Maximum Operating Temp., °F	230	158

**Values listed are typical for the material used in manufacture, except where noted, and are meant only as a guide to aid in design. Field testing should be performed to find the actual values for your application.

Custom Services

- Cut ■ Size ■ Color ■ Heat-Form ■ And More

Call for more information: **800-506-3924** or **215-526-2300**

Nylon-12 Tubing

NYLON-12 – Semi-rigid Grade

PART NO. <i>NATURAL</i>	PART NO. <i>BLACK</i>	ID (IN.)	OD (IN.)	WALL (IN.)	STANDARD LENGTH (FT.)	WORKING PSI AT 70°F	BURST PSI AT 70°F	BEND RADIUS* (IN.)	LBS. PER 100 FT.
233 0580	233 0531	.095	1/8	.015	500	400	1200	3/8	.25
233 0265	233 0216	.075	1/8	.025	500	1000	3000	1/4	.35
233 1210	233 1161	.106	5/32	.025	250	730	2200	3/8	.47
233 0895	233 0846	.086	5/32	.035	250	1120	3360	1/4	.60
233 1840	233 1791	.137	3/16	.025	250	530	1600	1/2	.58
233 1525	233 1476	.107	3/16	.040	250	980	2950	3/8	.84
233 2470	233 2421††	.190	1/4	.030	100, 250	500	1500	1	.95
233 2155	233 2106	.150	1/4	.050	250	1000	3000	1/2	1.39
233 3100	233 3051	.242	5/16	.035	100	465	1400	1-1/4	1.35
233 2785	233 2736	.182	5/16	.065	100	1165	3500	7/8	2.20
233 3730	233 3681	.295	3/8	.040	100	530	1600	1-1/2	1.92
233 3415	233 3366	.225	3/8	.075	100	1180	3550	1	3.20

*Use only as a guide.

††Limited stock item; lead times and minimums may apply — call for details.

Add length suffix to part number when ordering. Example: 250 ft. of .190" I.D. x 1/4" O.D., natural color tubing is number 233 2470-250.

BOLD indicates the critical dimension for fittings application.

NYLON-12 – Flexible Grade

PART NO. <i>NATURAL</i>	PART NO. <i>BLACK</i>	ID (IN.)	OD (IN.)	WALL (IN.)	STANDARD LENGTH (FT.)	WORKING PSI AT 70°F	BURST PSI AT 70°F	BEND RADIUS* (IN.)	LBS. PER. 100 FT.
234 0261	234 0212^^	.058	1/8	.034	100, 500	830	2500	5/16	.44
234 0576	234 0527**	.117	3/16	.035	100, 250	600	1800	3/8	.74
234 0891	234 0842	.170	1/4	.040	100, 250	450	1350	1/2	1.15
234 1521	234 1472^	1/4	3/8	1/16	100, 500	450	1350	1	2.69
234 1836	234 1787^	3/8	1/2	1/16	100, 500	330	1000	1-1/2	3.88
234 2151	234 2102	1/2	5/8	1/16	100	265	800	2-1/2	5.06
234 2466	234 2417	19/32	3/4	5/64	100	300	900	4	7.36
234 2781	234 2732	13/16	1	3/32	100	230	700	7	11.74

PART NO. <i>RED</i>	PART NO. <i>YELLOW</i>	PART NO. <i>GREEN</i>	PART NO. <i>BLUE</i>	ID (IN.)	OD (IN.)	WALL (IN.)	WORKING PSI AT 70°F	BURST PSI AT 70°F	BEND RADIUS* (IN.)	LBS. PER. 100 FT.
234 0289			234 0219	.058	1/8	.034	830	2500	5/16	.44
234 0604††	234 0625††	234 0569	234 0534††	.117	3/16	.035	600	1800	3/8	.74
234 0919	234 0940	234 0884	234 0849	.170	1/4	.040	450	1350	1/2	1.15
234 1549††	234 1570††	234 1514††	234 1479	1/4	3/8	1/16	450	1350	1	2.69
234 1864	234 1885		234 1794	3/8	1/2	1/16	330	1000	1-1/2	3.88

*Use only as a guide.

**Available in 250 ft. coils only.

^Available in 100 ft. coils only.

^^Available in 500 ft. coils only.

††Limited stock item; lead times and minimums may apply — call for details.

Red, Yellow, Green, and Blue sold by standard coil length only (100 ft.).

Add length suffix to part number when ordering. Example: 100 ft. of .058" I.D. x 1/8" O.D., red color tubing is part number 234 0289-100.

BOLD indicates the critical dimension for fittings application.

NYLON-12 – Metric Sizes, Flexible Grade

PART NO. <i>NATURAL</i>	PART NO. <i>BLACK</i>	PART NO. <i>RED</i>	PART NO. <i>YELLOW</i>	PART NO. <i>GREEN</i>	PART NO. <i>BLUE</i>	ID (MM)	OD (MM)	WALL (MM)	WORKING PSI AT 70°F	BURST PSI AT 70°F	BEND RADIUS* (MM)	LBS. PER. 100 FT.
236 0267	236 0211	236 0295	236 0309	236 0253	236 0225	2.5	4	.75	480	1450	8	.53
236 0897	236 0841	236 0925	236 0939	236 0883	236 0855	4	6	1	430	1300	13	1.06
236 1212	236 1156	236 1240	236 1254	236 1198	236 1170	6	8	1	315	950	33	1.49
236 1527	236 1471	236 1555	236 1569		236 1484	8	10	1	265	800	50	2.00
236 1842	236 1786	236 1877	236 1884††	236 1828	236 1800	9	12	1.5	300	900	45	3.32

*Use only as a guide.

††Limited stock item; lead times and minimums may apply — call for details.

All metric size tubing sold by standard coil length only (100 ft.). Add length suffix to part number when ordering. Example: 100 ft. of 2.5mm I.D. x 4mm O.D., natural color tubing is part number 236 0267-100.

Newloc® Push-to-Connect fittings are available from stock in metric sizes.

BOLD indicates the critical dimension for fittings application.



Newloc® Acetal Plastic Push-to-Connect Fittings

- Extremely easy to install — no tools necessary
- No flow restrictions
- Made from tough, lightweight, FDA-sanctioned materials
- Available in Fractional and Metric sizes
- Genuine John Guest brand fittings



Newloc Brass Brass Push-to-Connect Fittings

- Made of durable brass — elbows and tees are forged
- No flow restrictions
- Much higher temperature/pressure ratings than that of plastic
- All male pipe threads come with a pre-applied fluoropolymer sealant
- Easy to disconnect and reuse



Cutting Tools Two Sizes

- One for tubing up to 5/8" O.D.; another for sizes to 1-1/2" O.D.
- Both cut semi-rigid or soft tubing materials quickly and cleanly
- Lightweight, compact and durable
- Replaceable blade on larger size

Request a Semi-Rigid catalog

Inside you'll find details on all of NewAge Industries' Semi-Rigid tubing. Catalogs for PVC, polyurethane, fluoropolymer, silicone, and rubber tubing and hose are available, as well as barbed fittings and clamps, push-to-connect fittings, and custom products. Contact your NewAge Industries' sales representative or local distributor to request a copy of the catalog you need, or visit www.newageindustries.com.



Nylotube, Newloc, NewAge, "Fluid Transfer Specialists," and The "N" Logo are trademarks of NewAge® Industries, Inc.

WARRANTY: NewAge Industries' products are warranted to be free from defects in material and workmanship. Any product found to carry such defects will be replaced without charge. This warranty is limited only to the replacement of NewAge Industries' products, item for item, which after examination by NewAge Industries are deemed defective. NewAge Industries specifically disclaims any other liability. The data supplied is provided as a helpful guideline and is believed to be reliable; however, nothing stated shall constitute a guarantee, recommendation, or warranty for any application.

NOTICE: NewAge Industries, Inc. has been a privately owned corporation since 1954. Neither the corporation nor its principals are affiliated, in any way, with any other group or entity either representing themselves as or being referred to by the term New-Age.

© NewAge Industries, Inc. 2020 Specifications are subject to change without notice.

3/18/20

DISTRIBUTOR PARTNER



145 James Way
Southampton, PA 18966
www.newageindustries.com

800-50-NEWAGE
(800-506-3924)
215-526-2300
Fax: 800-837-1856
215-526-2190
info@newageindustries.com